

BRIGHTWELL

Datasheet



DrainWatch

DrainWatch is a durable and reliable dosing system suitable for indoor and outdoor applications that require the delivery of a single chemical at timed intervals.



Technical specifications	
Dimensions (Approx. mm)	Mains - 105 x 105 x 100 Battery - 105 x 210 x 100
Weight	Mains: 0.63 kg Battery: 0.75kg (excl. batteries)
Power	Mains: 100 - 240V AC 50/60Hz, Class II 9W Battery: 6VDC, 4 x D-Cell
Flowrate	10ml/min - 100ml/min*
Motor	DC Brushed motor (24VDC)
Operating Modes	20 events with duration from 5 sec to 3 min
Squeeze Tube Fittings	Compression fittings for 6mm OD tube
Enclosure	Polypropylene, IP65
Approvals	CE, CB Scheme
Warranty	1 year

Product box



DrainWatch unit
Silicone peristaltic tubing
Ceramic weight
Foot filter
LDPE tubing (3000mm)
Fixing pack (2 screws, 2 wall plugs)
HT5 Silicone grease (for peristaltic tubing)
Mounting bracket with spirit level
Drain pipe injector
Quick start guide

Part Numbers

DWB/D9	DrainWatch Battery
DWM/D9	DrainWatch Mains

Shipping info (Battery)

Shipping method	Quantity of units	Dimensions L x W x H (cm)	Net packed weight (kg)
Unit	1	31.5 x 16.5 x 16	1.7
Case	12	65.5 x 45.5 x 35	22
Pallet	144	133 x 111 x 122	249
Euro Pallet	48	120 x 80 x 86	85

Shipping info (Mains)



Shipping method	Quantity of units	Dimensions L x W x H (cm)	Net packed weight (kg)
Unit	1	17 x 13 x 16	1.2
Case	24	53.5 x 54.5 x 35	30
Pallet	288	113 x 116 x 123	351
Euro Pallet	96	120 x 80 x 86	142

*using water

BRIGHTWELL

Brightwell Dosing Ltd
Unit 1, Rich Industrial Estate
Avis Way, Newhaven
East Sussex, BN9 ODU

T: +44 (0)1273 513 566
E: sales@brightwell.co.uk

© 2024 Brightwell Dosing Ltd | Registered in England, Number 00661996.

