

BRIGHTWELL

Datasheet



EcoMix Compact

Ecomix proportioners provide an economical and flexible way of diluting chemicals on-site. Suitable for high flow applications, these proportioners are connected to the water mains and dilute a predetermined ratio of chemical concentrates into a ready-to-use solution.



Technical specifications

Dimensions (inches) (H x W x L)	8.66" x 3.75" x 5"
Weight	1.54 lbs.
Branding (cm) (H x W)	Branding plaque: Small: H 1.5 x W 3 Large: H 3 x W 4
Installation	Working temperature range 39.2° - 149° F Working pressure range 2 - 5 bar Minimum water flow required: High flow = 2.25 gal/min
Dilution	13 independent dilution ratios High Flow 6:1 - 350:1 Low Flow 2:1 - 128:1
Material	Cover/Backplate: Glass Bead Polypropylene (GBPP) Pusher: ABS Internal tubing and seals: EPDM



Approvals	WaterMark: Licence No. WMK25899 Specification: ATS5200.101-2005
Accessories	Hanging bracket Secure chemical cabinets (2L/5L) Colored rings
Warranty	2 years

In the box

EcoMix Compact Unit
Dispenser key
Ceramic weight
Foot valve
Low flow outlet tube with flood ring (LF/Bottle)
High flow 1.5m outlet tube with flood ring (HF/Bucket)
Clear PVC chemical suction tube - 6 x 9
Instruction manual
Drilling template
Screw pack
Bottle bracket and clips (low flow version)
Bucket hook (high flow version)

Part numbers

Part number	Description
DPCHB-WK	EcoMix Compact HF/Bucket, White Cover, Grey Ring
DPCLBB-WK	EcoMix Compact LF/Bottle, White Cover, Grey Ring

Shipping info



Shipping method	Quantity of units	Dimensions L x W x H (inches)	Net packed weight (lbs.)
Unit	1	14.5" x 6.25" x 6"	3 lbs.
Case	12	25.5" x 21.25" x 20.5"	37.5 lbs.
Pallet	108	47.25" x 39.5" x 46"	379 lbs.
Euro Pallet	84	47.25" x 31.5" x 43.75"	315 lbs.

BRIGHTWELL

Brightwell Dispensers Inc.
9858 Britton Street
Lenexa, KS
66219

T: (+1) 913-956-4909
E: sales@brightwell-inc.com

© 2024 Brightwell Dosing Ltd | Registered in England, Number 00661996.

